





Specification

- Probe Type: Convex, Linear,
- Scanning mode: Electronic array
- Display mode: B, B/M, color doppler version with B+Color, B+PDI, B+PW
- Probe element: 128/192
- Channel of RF circuit board: 32/64
- Probe frequency and scan depth, head radius/width,
Convex head 3.5MHz/5MHz, 90/160/220/305mm,
scan angle(convex):60mm, 60°
- Linear head 7.5MHz/10MHz, 20/40/60/100mm,
scan angle(linear): 40mm
- Image Adjust: BGain, TGC, DYN, Focus, Depth, Harmonic, Denoise, Color Gain, Steer, PRF
- Cineplay: auto and manual, frames can set as 100/200/500/1000
- Puncture assist function: the function of in-plane puncture guide line, out-of-plane puncture guide line, automatic blood vessel measurement.
- Measure: Length, Area, Angle, heart rate, Obstetrics
- Image save: jpg, avi and DICOM format
- Image frame rate: 18 frames/second
- Battery working time: 2.5 hours(according to whether keep scan)
- Battery charge: by USB charge or wireless charge, take 2 hours
- Dimension: L156×W60×H20mm(if with transvaginal head length is 270mm)
- Weight: 250g
- Wifi type: 802.11g/20MHz/5G/450Mbps
- Working system: Apple iOS and Android,

